



# BEGA

Photometric Filename: 33379.IES

TEST: BE\_33379  
 TEST LAB: BEGA  
 DATE: 2/14/2017  
 LUMINAIRE: 33 379  
 LAMP: 70W LED  
 (43.4W LED up)  
 (26.6W LED down)




\*Preliminary Data

## Characteristics


Distribution Type	Type II (Down) Wall Wash (Up)
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	8963
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	112
Total Luminaire Watts	80
Ballast Factor	1.00
Upward Waste Light Ratio	0.59
Max. Cd.	4876 (180H, 167.5V)
Max. Cd. (<90 Vert.)	1684.3 (295H, 52.5V)
Max. Cd. (At 90 Deg. Vert.)	3 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	435 (4.9%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)

## Zonal Lumen Summary

Zone	Lumens
0-10	94.92
10-20	283.90
20-30	452.46
30-40	583.28
40-50	672.55
50-60	675.25
60-70	549.72
70-80	299.78
80-90	64.47
90-100	2.94
100-110	138.79
110-120	501.77
120-130	750.31
130-140	924.34
140-150	991.15
150-160	937.22
160-170	778.52
170-180	261.94



Wall Mount Fixture - Isofootcandle Grid on Floor  
 Mounting Height = 20 ft. Grid Spacing = 20 ft.



Wall Mount Fixture - Isofootcandle Grid on Wall  
 Grid Spacing = 10 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

3/22/2018