

Application

This LED wall luminaire with an asymmetric light distribution can be used to illuminate ceiling or ground surfaces in front of the mounting surface. Can be used for uplight or downlight applications.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Clear safety glass
 Reflector made of pure anodized aluminum
 Silicone applied robotically to casting, plasma treated for increased adhesion
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65
 Weight: 11 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	43.4 W
System wattage	50 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	4549 lumens (3000K)
Lifetime at Ta = 15° C	50,000 h (L70)

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED wall luminaire · asymmetric light distribution

	LED	A	B	C
33386	43.4 W	12 1/2	5	8 5/8

Type:
 BEGA Product:
 Project:
 Modified:

