

Application

This LED wall mounted luminaire has light output on one side. Thick-walled crystal glass characterizes the design of this distinctive luminaire. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Crystal glass, inside white
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64
Weight: 3.1 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	8.2 W
System wattage	10 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	420 lumens (3000K)
Lifetime at Ta = 15° C	>500,000 h (L70)
Lifetime at Ta = 50° C	137,000 h (L70)

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



LED wall luminaire · light output on one side				
	LED	A	B	C
33 449	8.2 W	4 ¾	5 ½	5 ½

Type:
BEGA Product:
Project:
Modified:

