

**Application**

This is a shielded LED wall mounted luminaire featuring a half lid and guard. Arranged individually or in groups, they are great design elements for a host of lighting applications.

**Materials**

Luminaire housing and guard constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Borosilicate glass with optical texture  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP65  
 Weight: 5.7 lbs

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	3.9W
System wattage	6W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	245 lumens (3000K)
Lifetime at Ta = 15° C	>500,000 h (L70)
Lifetime at Ta = 45° C	463,000 h (L70)

**LED color temperature**


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



**LED wall luminaire · shielded**

	LED	A	B
<b>33 529</b>	3.9W	10 1/4	6

Type:  
 BEGA Product:  
 Project:  
 Modified:

