


# BEGA

Photometric Filename: 33533.IES

TEST: BE\_33533  
 TEST LAB: BEGA  
 DATE: 10/26/2017  
 LUMINAIRE: 33 533  
 LAMP: 0.95W LED, 24 VDC




## Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	97
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	32
Total Luminaire Watts	3
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.38
Spacing Criterion (90-270)	1.38
Spacing Criterion (Diagonal)	1.52
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.28 ft (Diameter)
Luminous Height	0.07 ft

## Zonal Lumen Summary

Zone	Lumens
0-10	2.14
10-20	6.27
20-30	9.88
30-40	12.54
40-50	13.99
50-60	13.97
60-70	12.41
70-80	9.43
80-90	5.50
90-100	3.07
100-110	2.30
110-120	2.44
120-130	1.88
130-140	0.96
140-150	0.22
150-160	0.00
160-170	0.00
170-180	0.00



Ceiling Mount - Isofootcandle grid on floor  
 Mounting Height = 10 ft. Grid Spacing = 2.5 ft.



Wall Mount - Isofootcandle grid on floor  
 Mounting Height = 5 ft. Grid Spacing = 2.5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.