

Application

The material thickness and strong crystal glass makes this impact-resistant LED luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
Heavy pressed crystal glass, inside white  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 0.9lbs

Electrical

Operating voltage	24VDC (remote power supply req.)
LED module wattage	0.95 W
System wattage	3 W
Color rendering index	Ra > 90
Luminaire lumens	97 lumens (3000K)
Lifetime at Ta = 15° C	50,000 h (L70)

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:  
BEGA Product:  
Project:  
Modified:

Available Accessories

**19591** Remote 50W LED driver and box  
**19580** Remote 25W LED driver and box  
See individual accessory spec sheet for details.



LED ceiling and wall luminaire · unshielded				
	LED	A	B	Required wiring box
33 533 <b>ADA</b>	0.95 W	4	2	19 538

