

**Application**  
LED ceiling and wall luminaire with hand-blown, three-ply opal glass. This luminaire can be utilized individually or in groups for glare-free illumination of interior and exterior spaces.

**Materials**  
Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Three-ply opal glass satin matte finish  
High temperature silicone gasket

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 64  
Weight: 4.4 lbs

**Electrical**  
Operating voltage120-277V AC  
Minimum start temperature-30° C  
LED module wattage14.2 W  
System wattage17 W  
Controllability0-10V dimmable  
Color rendering indexRa > 90  
Luminaire lumens1066 lumens (3000K)  
Lifetime at Ta = 15° C>500,000 h (L70)  
Lifetime at Ta = 35° C194,000 h (L70)


**LED color temperature**  
4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:  
BEGA Product:  
Project:  
Modified:



LED ceiling and wall luminaire · unshielded			
	LED	A	B
33 636	ADA 14.2 W	10 3⁄8	3 1⁄8

