

Application

LED ceiling and wall luminaire with shallow profile designed for general purpose illumination featuring hand-blown, three-ply opal glass. This luminaire can be utilized individually or in groups for glare-free illumination in interior and exterior spaces.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Three-ply opal glass satin matte finish  
High temperature silicone gasket

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 64  
Weight: 6.6lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	19.6 W
System wattage	23 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	2094 lumens (3000K)
Lifetime at Ta = 15° C	>500,000 h (L70)
Lifetime at Ta = 45° C	99,000 h (L70)

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:  
BEGA Product:  
Project:  
Modified:



LED ceiling and wall luminaire			
	LED	A	B
33681	ADA 19.6 W	12	2 5/8

