

Application

LED ceiling and wall luminaires designed for the illumination of rooms, bathrooms, stairways, and other interior spaces characterized by their shallow projection featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

Luminaire housing constructed of aluminum alloy with painted white finish  
Three-ply opal glass satin matte finish  
Optionally available with synthetic diffuser for impact protection, specify luminaire with 'P' suffix

NRTL listed to North American Standards, suitable for damp locations  
Weight: 6.0lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	16.4 W
System wattage	18.9W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,601 lumens (3000K)
Lifetime at Ta = 15° C	500,000 h (L70)
Lifetime at Ta = 40° C	109,000 h (L70)

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White painted finish

Type:  
BEGA Product:  
Project:  
Modified:



LED ceiling and wall luminaire					
		LED	A	B	C
34 287	ADA	16.4 W	13 3⁄8	3 3⁄8	10 1⁄2

