

Application

LED ceiling and wall luminaires designed for the illumination of rooms, bathrooms, stairways, and other interior spaces characterized by their shallow projection featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

Luminaire housing constructed of aluminum alloy with painted white finish
Three-ply opal glass satin matte finish
Optionally available with synthetic diffuser for impact protection, specify luminaire with 'P' suffix

NRTL listed to North American Standards, suitable for damp locations
Weight: 6.0lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	25.9 W
System wattage	31.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	2,100 lumens (3000K)
Lifetime at Ta = 15° C	271,000 h (L70)
Lifetime at Ta = 40° C	64,000 h (L70)

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White painted finish

Type:
BEGA Product:
Project:
Modified:



LED ceiling and wall luminaire				
	LED	A	B	C
34 288	ADA 25.9 W	15 3⁄8	3 1⁄2	11 7⁄8

