

Application

LED ceiling luminaires with dual light distribution. Hand-blown, partially frosted crystal glass with a concave bottom side for soft and pleasant uniform distribution of the light. A reflector on the inside directs part of the light onto the ceiling surface. Designed for the illumination of public or private rooms, stairways, and hallways with a high level of visual comfort.

Materials

Luminaire housing constructed of die-cast aluminum alloy with painted white, stainless steel, or polished aluminum finish
 Partially frosted crystal glass
 Reflector made of pure anodized aluminum
 Silicone optical lens
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for damp locations
 Weight: 3.5lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	17.8W
System wattage	21.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1,478 lumens (3000K)
Lifetime at Ta = 15° C	260,000 h (L70)
Lifetime at Ta = 30° C	190,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available finishes	White	Code number .1
	Stainless steel	Code number .2
	Polished aluminum	Code number .3



Interior LED ceiling luminaires · dual light distribution

	LED	A	B
50061.1	17.8W	7 1/2	5 1/4

Type:
 BEGA Product:
 Project:
 Modified:

