

LIMBURG Collection

LED luminaires with dual light distribution

**Material:** Luminaire housing constructed of aluminum with white, stainless steel, or polished aluminum finish. Pure anodized aluminum reflector. Designed for attachment to wall or ceiling over standard 4" octagonal wiring box (by others).

**Glass:** Hand-blown, partially frosted crystal glass with thread.

**Electrical:** 25.4 LED luminaire, 30.0 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI Available in 4000K (>80 CRI); add suffix K4 to order.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com)

**Finish:** Select the desired material finish using the appropriate code number as a suffix.

- White Code number **.1**
- Stainless steel Code number **.2**
- Polished aluminum Code number **.3**

**CSA** certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.

**Weight:** 4.6 lbs

**Luminaire Lumens:** 2236 lumens

Type:  
LIMBURG Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



LED ceiling luminaires				
	Finish	LED	A	B
50 062.1	White	25.4 W	8 5/8	6 1/8
50 062.2	Stainless steel	25.4 W	8 5/8	6 1/8
50 062.3	Polished aluminum	25.4 W	8 5/8	6 1/8