


BEGA

Photometric Filename: 50068.IES

TEST: LI_50068
TEST LAB: BEGA
DATE: 3/24/2016
LUMINAIRE: 50 068.X
LAMP: 19.6W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2109
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	88
Total Luminaire Watts	24
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.26 ft (Diameter)
Luminous Height	1.79 ft

Zonal Lumen Summary

Zone	Lumens
0-10	1.20
10-20	11.70
20-30	36.31
30-40	72.26
40-50	114.58
50-60	157.68
60-70	196.10
70-80	224.80
80-90	239.72
90-100	239.72
100-110	224.80
110-120	196.10
120-130	157.68
130-140	114.58
140-150	72.26
150-160	36.31
160-170	11.70
170-180	1.20



Mounting Height = 5 ft. Grid Spacing = 10 ft.
Isofootcandle grid on floor



Grid Spacing = 2.5 ft.
Isofootcandle grid on wall

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

9/28/2018