

# LIMBURG Collection

## LED wall luminaire

**Material:** Luminaire housing and end caps constructed of aluminum with stainless steel or chrome finish. Designed for attachment to wall over BEGA 19 537 small opening wiring box (provided).

**Glass:** Hand-blown, three-ply opal glass

**Electrical:** 23.6W LED luminaire, 27.5 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI. Available in 4000K (>80 CRI); add suffix K4 to order.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).


**Finish:** Select the desired material finish by using the appropriate code number as suffix.

- Stainless steel Code number **.2**
- Chrome Code number **.3**

**CSA** certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.

**Weight:** 7.3 lbs.

**Luminaire lumens:** 2620



An internal mechanism allows the glass to be swivelled in and out in order to change the lamp. This means that they can also be installed in niches from wall to wall, optionally in horizontal or vertical position.



### Wall luminaires

	Finish	Lamp		A	B	C	Required wiring box
<b>50 069.2</b>	Stainless steel	23.6W LED		27 <sup>3</sup> / <sub>4</sub>	3 <sup>1</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>2</sub>	<b>19 537</b>
<b>50 069.3</b>	Chrome	23.6W LED		27 <sup>3</sup> / <sub>4</sub>	3 <sup>1</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>2</sub>	<b>19 537</b>

Type:  
 LIMBURG Product:  
 Project:  
 Voltage:  
 Color:  
 Options:  
 Modified:

