

LIMBURG Collection

LED wall luminaire

**Material:** Luminaire housing constructed of metal with white painted finish. Designed for attachment to wall over BEGA 19 537 small opening wiring box (provided).

**Glass:** Hand-blown, three-ply opal glass

**Electrical:** 30.0W LED luminaire, 35.6 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI. Available in 4000K (>80 CRI); add suffix K4 to order.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Finish:** White painted finish.

**CSA** certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.

**Weight:** 6.6 lbs.

**Luminaire lumens:** 3311

Type:  
LIMBURG Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



Wall luminaires					
	LED	A	B	C	Required wiring box
50 084.1	30.0 W	4	24	5 3/8	19 537