


BEGA

Photometric Filename: 50216.IES

TEST: LI_50216
TEST LAB: BEGA
DATE: 10/27/2016
LUMINAIRE: 50 216
LAMP: 35.2W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5070
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	124
Total Luminaire Watts	41
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Hor. Cylinder
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	3.31 ft
Luminous Height	0.28 ft (Diameter)

Zonal Lumen Summary

Zone	Lumens
0-10	53.60
10-20	156.21
20-30	244.69
30-40	312.14
40-50	355.37
50-60	374.19
60-70	371.81
70-80	356.04
80-90	339.05
90-100	336.97
100-110	350.52
110-120	363.97
120-130	364.96
130-140	345.78
140-150	303.28
150-160	237.43
160-170	151.64
170-180	52.27



Wall Mount (Vertical) *Isofootcandle grid on wall
Grid Spacing = 5 ft.



Wall Mount (Vertical) *Isofootcandle grid on floor
Mounting Height = 8 ft. Grid Spacing = 10 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2016

11/3/2016