

Application

Portable LED luminaires for the private home and garden. These unshielded luminaires create a pleasant light effect and are provided with an earth spike for portability.

Materials

Luminaire housing constructed of reinforced polyamide with earth spike
 Three-ply opal glass with screw neck
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 2.6lbs

Electrical

Operating voltage	Magnetic 12VAC
Minimum start temperature	-40° C
LED module wattage	1.9W
System wattage	2.5W
Color rendering index	Ra > 80
Luminaire lumens	245 lumens (3000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**
- Amber - Product number + **AMB**

Wildlife friendly amber LED - Optional


Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.

LED module wattage	2.1 W (Amber)
System wattage	2.9W (Amber)
Luminaire lumens	92 lumens (Amber)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Synthetic housing provided in standard BEGA Graphite. Custom colors not available.



Garden luminaire with earth spike				
	LED	A	B	C
55 030	1.9W	5 7/8	10 1/8	7 5/8

Type:
 BEGA Product:
 Project:
 Modified:

Available Accessories

536 300VA 12AC Transformer

See individual accessory spec sheet for details.

