

LIMBURG Collection

Pendant luminaire with crystal glass and downward directed light

Material: Luminaire housing and canopy constructed of metal with white, stainless steel, or polished aluminum finish. White luminaires with white connecting cable, stainless and polished aluminum luminaires with black connecting cable. Reflector made of high-gloss anodized aluminum. Designed for attachment to ceiling over standard 4" octagonal wiring box (by others).

Note: Pendant luminaire 56 565.1 with white finish is supplied with a reflector with white finish.

Glass: Hand-blown crystal glass. Additional focusing/dispersing lens made of frosted crystal glass.

Electrical: 19.0W LED luminaire, 23 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver located in canopy, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI Available in 4000K (>80 CRI); add suffix K4 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: Select the desired material finish by using appropriate code number as suffix

- White Code number **.1**
- Stainless steel Code number **.2**
- Polished aluminum Code number **.3**

CSA certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.

Weight: 5.5 lbs

Type:
LIMBURG Product:
Project:
Voltage:
Color:
Options:
Modified:



Crystal glass + reflector						
	Finish	LED	β	A	B	L
56 565.1	White	19.0W	36°	7 7/8	8 7/8	79
56 565.2	Stainless steel	19.0W	36°	7 7/8	8 7/8	79
56 565.3	Polished aluminum	19.0W	36°	7 7/8	8 7/8	79

β =beam angle