

LIMBURG Collection

Shielded LED pendant luminaires

Material: Luminaire housing and canopy constructed of metal with velvet black painted exterior finish and black connecting cable. Interior finish is aluminum, copper or brass.

Glass: Internal hand-blown opal glass

Electrical: 8.9W LED luminaire, 11 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver located in canopy, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI Available in 4000K (>80 CRI); add suffix K4 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Options: Optionally available with a low profile canopy, specify LPC.

Finish: Select the desired material finish by using appropriate code number as suffix


- Velvet black · Matte aluminum Code number **.2**
- Velvet black · Matte brass Code number **.4**
- Velvet black · Matte copper Code number **.6**

CSA CSA certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.


Weight: 5.3 lbs.

L = overall length of luminaire


Canopy Options:



Standard canopy - designed for attachment to ceiling over standard 4" octagonal wiring box (by others).



Low profile canopy - includes required custom recessed junction box to house LED driver



Velvet black				
	Finish	LED	A	B
56 614.2	Matte aluminum	8.9W	5 3/4"	6 1/2"
56 614.4	Matte brass	8.9W	5 3/4"	6 1/2"
56 614.6	Matte copper	8.9W	5 3/4"	6 1/2"

Type:
LIMBURG Product:
Project:
Voltage:
Color:
Options:
Modified:

