

LIMBURG Collection

FLED - LED large area pendant luminaires with direct and indirect light

Material: The luminaire housing and ceiling canopy constructed of aluminum with matte aluminum finish. Luminaire housing with continuous black metal strip. Steel wires with black connecting cable. Ceiling canopy designed for attachment to ceiling over BEGA 19 537 narrow opening wiring box.

Diffuser: Micro-structured acrylic diffuser with light-directing reflection layers, 70% downward directed light and 30% indirect light.

Electrical: 52.6W LED luminaire, 60.0 total system watts, -40°C start temperature. 120V through 277V LED driver located in canopy, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI Available in 4000K (>80 CRI); add suffix K4 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.


Finish: Matte aluminum finish with continuous matte black strip.

CSA certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.

Weight: 26.5 lbs.

Luminaire Lumens: 7085 lumens

Type:
 LIMBURG Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



Pendant luminaire with 70% direct and 30% indirect light

	LED	A	B	C	L
56624.2	52.6W	61 3/4	5/8	13 1/2	79