

Application

This LED wall luminaire has a partially shielded light source and is designed for the down lighting of interior and exterior locations with glare-free illumination.

Materials

Luminaire housing constructed of die-cast and spun marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Three-ply opal glass
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44
Weight: 3.3lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	8.9W
System wattage	12W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	722 lumens (3000K)
Lifetime at Ta = 15° C	500,000 h (L70)
Lifetime at Ta = 40° C	268,000 h (L70)

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



LED wall luminaire · partially shielded					
	LED	A	B	C	D
66410	8.9W	10 ¼	10 ⅞	12 ⅜	4 ⅜

Type:
BEGA Product:
Project:
Modified:

