

Application

LED wall mount luminaire with asymmetrical light distribution designed for the illumination of parking areas and roadways.

Materials

Luminaire housing and mounting canopy constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Clear safety glass with anti-reflective coating for increased transmission  
Reflector made of pure anodized aluminum  
Silicone applied robotically to casting, plasma treated for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 66  
Weight: 9.3lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	31.5 W
System wattage	37.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	4,741 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Wall mount luminaire - Asymmetrical light distribution					
	LED	A	B	C	D
66 451	31.5 W	10	2 3/8	16 1/8	5 1/8

Type:  
BEGA Product:  
Project:  
Modified:

