

Wall luminaires with single-sided light output

Housing: Extruded and die cast aluminum. Mounts directly to a BEGA 19537 box (provided). Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Tempered, clear glass, flush to the die casting to prevent water accumulation. Fully gasketed for weather tight operation using a 'U' channel molded silicone rubber gasket.

Electrical: 12.5W LED luminaire, 15.9 total system watts, -40°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V, TRIAC, and ELV dimmable. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with an 85 CRI. Available in 4000K (85 CRI); add suffix K4 to order.

Notes: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.



CSA certified to U.S. and Canadian standards for wet locations.
Protection class IP65

Weight: 7.3 lbs

Luminaire Lumens: 1258

Mounting options:

79547 Surface-mount wiring box



These luminaires mount over a custom BEGA recessed box. This box can be shipped ahead of the luminaire.

Narrow beam upwards or downwards

|  | Lamp | β | A | B | C | D | Wiring box* |
|---|----------------|-----------|-------|-----------------|------------------|-----------------|-----------------|
| | 66 698* | 12.5W LED | 19.5° | 5 $\frac{7}{8}$ | 11 $\frac{3}{4}$ | 7 $\frac{7}{8}$ | 1 $\frac{5}{8}$ |

β = Beam angle *Small opening wiring box included.

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:

