

## Pole top luminaires with symmetrical light distribution

**Housing/fitter:** Die-cast aluminum construction with a spun aluminum cap. The fixture slip fits a 3" O.D. pole top or tenon and is secured by four (4) socket head stainless steel set screws threaded into stainless steel inserts. Die castings are marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy.

**Enclosure:** Molded  $\frac{1}{8}$ " clear high impact acrylic lens with white, aluminum louver stack.

**Electrical:** 23.4W LED luminaire, 27 total system watts,  $-30^{\circ}\text{C}$  start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. Standard LED color temperature is 4000K with a  $>80$  CRI. Available in 3000K ( $>80$  CRI); add suffix K3 to order.

**Note:** Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.


**UL** listed for US and Canadian Standards, suitable for wet locations. Protection class: IP65.

**Weight:** 22.0 lbs.

**EPA (Effective projection area):** 1.3 sq. ft.

**Luminaire Lumens:** 1697

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



	Lamp	A	B
77 142	23.4 W LED	25%	23 $\frac{5}{8}$

\*recommended for use with 8' to 12' poles

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 FAX (805) 566-9474 [www.bega-us.com](http://www.bega-us.com)

©copyright BEGA 2019 Updated 01/18/2019