

## LED garden and pathway bollard

**Post construction:** One piece extruded aluminum. All aluminum in the construction is marine grade and copper free.

**Lamp Enclosure:** One piece die cast aluminum housing attached to post using two (2) captive stainless steel screws threaded into stainless steel inserts. Matte safety glass lens. Fully gasketed using a one piece molded silicone gasket.

**Electrical:** 2.1W LED luminaire, 3.4 total system watts, -30°C start temperature. Integral 12V AC driver provided must be operated using remote magnetic transformer. Standard LED color temperature is 3000K with a >90 CRI.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Anchor base:** Anchor base made of galvanized steel, made for bolting into foundation or other paved surface. Bollards are secured to anchor base using two (2) stainless steel set screws.


**Finish:** Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**Please note:** BEGA's approach to product design is to innovate, not follow. With a steadfast commitment to quality, each product is conceived to satisfy a general or specific lighting task as defined by its architectural or exterior surroundings. The Home and Garden Collection is designed specifically for use in Residential and Light Commercial applications. Please reference our standard BEGA portfolio when mounting provisions for the rigorous demands of high-use commercial and/or vandal prone settings are required.

**CSA certified** to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

**Weight:** 6.3 lbs.

Type:  
 BEGA Product:  
 Project:  
 Voltage:  
 Color:  
 Options:  
 Modified:



		Lamp	A	B	C
<b>77 264</b>	with hardscape base	2.1 W LED	4 <sup>3</sup> / <sub>8</sub>	27 1/2	4 <sup>3</sup> / <sub>8</sub>