

Application

Twin head bollard with shielded, direct light for illuminating entrances, paths, and many areas of public and private spaces. These luminaires provide glare-free illumination with a high degree of visual comfort for uniform lighting of ground surfaces.

Materials

Luminaire housing and base constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Impact resistant polycarbonate diffuser
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65
 Weight: 13.7 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	15.6 W
System wattage	20.0 W
Controllability	Dimming not available
Color rendering index	Ra > 90
Luminaire lumens	1248 lumens (3000K)
LED service life (L70)	60,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Bollard - shielded, directed light					
	LED	A	B	C	Anchorage
77 321	15.6 W	7 1/2	39 1/2	18 5/8	79 817

Type:
 BEGA Product:
 Project:
 Modified:

