

Application

LED pole-top luminaire with asymmetric wide spread light distribution designed to illuminate roadways, squares, driveways and pedestrian areas. Tool-less entry for ease of maintenance. Provided with slip fitter to fit 3" O.D. poles.

Materials

Luminaire housing and pole fitter constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Clear acrylic diffuser with optical texture  
Reflector made of pure anodized aluminum  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 66

Weight: 19.4 lbs.

EPA (Effective projection area): 0.75 sq. ft.

Electrical

Operating voltage	120-277VAC (surge protection)
Minimum start temperature	-30° C
LED module wattage	57.4 W
System wattage	65.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	6,781 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



Pole-top luminaire · asymmetric wide spread				
	LED	A	B	C
77 520	57.4 W	15 3⁄8	5 3⁄8	29 1⁄2

Recommended for use with 16' to 20' poles

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2018 Updated 01/17/19

Type:  
BEGA Product:  
Project:  
Modified:

