

Small scale LED floodlights with I.P.S. nipple - very narrow beam

Housing: Luminaire constructed of a one piece die-cast aluminum housing. LED module paired with inner reverse-tapered casting to provide maximum heat transfer to outer housing. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Luminaire's optical system consists of a reflector of pure anodized aluminum and clear safety glass with an integrated stray light control cylinder and a glass optic. The lens and optical assembly is secured by a die cast aluminum trim ring using (3) stainless steel captive fasteners.

Mounting: Provided with a 1/2" I.P.S. stainless steel nipple for direct attachment to cast boxes or other accessories.

Electrical: 12.5W LED luminaire, 15 total system watts, -40°C start temperature. Integral 120V-277V electronic LED driver, 0-10V, TRIAC and ELV dimmable. The LED module and driver are mounted on a removable inner assembly for easy replacement. Standard LED color temperature is 4000K with an 80 CRI. Available in 3000K (80 CRI); add suffix K3 to order.

Note: Due to the dynamic nature of LED technology, LED luminaire data in this catalog is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. These luminaires are available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

CSA: Certified to U.S. and Canadian standards for wet locations.


Protection class IP65.

Weight: 4.9 lbs.

EPA: 0.29 sq. ft.

Luminaire Lumens: 1132

Type:
 BEGA Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



Compact floodlight · very narrow beam		Accessories					
Lamp	β	A	B	C			
77 703 12.5W LED	9°	6 1/4"	8 1/2"	6 1/2"			
					70 076	70 757	70 720

Exchangeable lenses flat beam 180° glare shield 360° glare shield β = Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 FAX (805) 566-9474 www.bega-us.com

©copyright BEGA 2019 Updated 03/15/2019

