

## Pole top luminaires with asymmetrical wide spread light distribution

**Housing:** Die-cast aluminum housing and slip fitter. Slip fits 3" O.D. pole top, secures to pole with six stainless steel set screws. Die-cast aluminum knuckle allows for 0° or 15° tilt adjustment from horizontal. Die castings are marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy.

**Enclosure:** Faceplate is constructed of die-cast aluminum and can be opened without tools for easy maintenance. Clear acrylic diffuser with optical texture. Fully gasketed with a molded silicone gasket.

**Electrical:** 26.6W LED luminaire, 31.1 total system watts, -30° C start temperature. Integral 120V through 277 V electronic LED driver, 0-10V dimming\*. Standard LED color temperature is 4000K with a  $>80$  CRI. Available in 3000K ( $>80$  CRI); add suffix K3 to order.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. These luminaires are available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

UL listed for US and Canadian Standards, suitable for wet locations.  
Protection class: IP66.



**Weight:** 16.5 lbs.

**EPA (Effective projection area):** 0.8 sq. ft.

**Luminaire Lumens:** 1814

Tested in accordance with LM-79-08

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



### Single pole-top luminaires

	Lamp	A	B	C
<b>77834</b>	26W LED	29 1/2"	15 3/8"	5 3/8"

Recommended for use with 14' to 16' poles.

**BEGA-US** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 FAX (805) 566-9474 [www.bega-us.com](http://www.bega-us.com)

©copyright BEGA-US 2016 Updated 01/19