



BEGA

Photometric Filename: 77834.ies

TEST: 20626
 TEST LAB: LUMINAIRE TESTING LABORATORY, INC.
 DATE: 3/19/2011
 LUMINAIRE: 77 834
 LAMP: 26W LED

All results in accordance with IESNA LM-79-08




Characteristics

IES Classification	Type III
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1814
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	58
Total Luminaire Watts	31.1
Ballast Factor	1.00
Upward Waste Light Ratio	0.02
Max. Cd.	531.85 (85H, 43V)
Max. Cd. (<90 Vert.)	531.85 (85H, 43V)
Max. Cd. (At 90 Deg. Vert.)	74.19 (4.1%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	240.71 (13.3%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	154.9	N.A.	8.5
FM (30-60)	430.6	N.A.	23.7
FH (60-80)	257.1	N.A.	14.2
FVH(80-90)	54.3	N.A.	3.0
BL (0-30)	155.5	N.A.	8.6
BM (30-60)	431.3	N.A.	23.8
BH (60-80)	249.9	N.A.	13.8
BVH(80-90)	51.4	N.A.	2.8
UL (90-100)	26.2	N.A.	1.4
UH (100-180)	2.4	N.A.	0.1
Total	1813.6	N.A.	100.0

BUG Rating B1-U2-G1



Mounting Height = 12 ft. Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2015

8/11/2015