

Pole top luminaires with asymmetrical wide spread light distribution

**Housing:** Die-cast aluminum housing and slip fitter. Slip fits 3" O.D. pole top, secures to pole with six stainless steel set screws. Die-cast aluminum knuckle allows for 0° or 15° tilt adjustment from horizontal. Die castings are marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy.

**Enclosure:** Faceplate is constructed of die-cast aluminum and can be opened without tools for easy maintenance. Clear acrylic diffuser with optical texture. Fully gasketed with a molded silicone gasket.

**Electrical:** 104 W LED luminaire, (50.6W per head) total system watts, -30° C start temperature. Integral 120 V through 277 V electronic LED driver. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. These luminaires are available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**UL** listed for US and Canadian Standards, suitable for wet locations.  
Protection class: IP66.



**Weight:** 31.0 lbs.

**EPA (Effective projection area):** 1.5 sq. ft.

**Luminaire Lumens:** 9769 total • 4898 per head

Tested in accordance with LM-79-08

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



Twin pole-top luminaires

Lamp	A	B	C
77 841 (2) 50.6W LED	55	15 ⅜	5 ⅜
Recommended for use with 20' to 30' poles.			