

Twin LED pole top luminaires with asymmetrical wide beam light distribution

Housing: Die-cast aluminum housing and slip fitter. Slip fits 3" O.D. pole top, secures th pole with integrated slip fitter mechanism and single set screw. Die castings are marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy.

Enclosure: Faceplate is hinged; constructed of die-cast aluminum with toolless access latch for easy maintenance. Tempered clear safety glass with an anti-reflective coating. Optical reflector of pure anodized aluminum. Fully shielded light distribution for no trespass above horizontal. Fully gasketed for weather tight operation using molded silicone gasket.

Electrical: 101.2W LED luminaire (50.6W per luminaire head), 114.0 total system watts, -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. Integral surge protection to protect the luminaire against surges rated up to 10kV. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.


CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP66

Weight: 21.6 lbs.

EPA (Effective projection area): 0.53 sq. ft.

Luminaire Lumens: 9054

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



Twin pole-top luminaires			
Lamp	A	B	C
77 859	2 50.6W LED	10 ¼ 2 ¼	41