

Pole top luminaires with asymmetrical flat beam light distribution

Housing/fitter: One piece heavy die-cast aluminum construction with swivel arm and internal full semi specular anodized aluminum reflectors. Swivel arm allows for 0° to 15° aiming positions. Integral fitter slip fits 3" O.D. pole top and is secured by eight (8) socket head stainless steel set screws threaded into stainless steel inserts. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Door frames are die-cast, hinged and latched for toolless entry. Lens is $\frac{1}{8}$ " clear tempered glass, sealed with one piece silicone gasket.

Electrical: 15.8W LED luminaire, 20 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

Note: Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. These luminaires are available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.



UL listed for US and Canadian Standards, suitable for wet locations, Protection class IP66.

Weight: 18.4 lbs.

EPA (Effective projection area): 0.65 sq. ft.

Luminaire Lumens: 2160

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



Single pole-top luminaires

	Lamp	LEED	A	B	C
77 928	15.8W LED	LZ-1	11½	4¼	23⅞

Recommended for use with 14' to 25' poles.

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 FAX (805) 566-9474 www.bega-us.com

©copyright BEGA 2019 Updated 01/16/2019