

Application

LED luminaires with impressive crystal glass designed for general purpose illumination for interior spaces, featuring a shallow depth. The white interior of the glass appears to be embedded in the clear crystal glass. Whether as individual luminaires or arranged in groups, this series enhances any interior.

Materials

Luminaire housing constructed of pressed steel with white painted finish  
Crystal glass, inside white

**NRTL** listed to North American Standards, suitable for damp locations  
Weight: 5.5lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	10.6W
System wattage	12.5W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	840 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 55° C	210,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:  
BEGA Product:  
Project:  
Modified:



Interior LED ceiling and wall luminaires				
		LED	A	B
78634	ADA	10.6W	9 3⁄4	3 1⁄2

