

Application

LED luminaires with impressive crystal glass designed for general purpose illumination for interior spaces, featuring a shallow depth. The white interior of the glass appears to be embedded in the clear crystal glass. Whether as individual luminaires or arranged in groups, this series enhances any interior.

Materials

Luminaire housing constructed of pressed steel with white painted finish
Crystal glass, inside white

NRTL listed to North American Standards, suitable for damp locations
Weight: 7.7lbs

Electrical


Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	11.6W
System wattage	14.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,141 lumens (3000K)
Lifetime at Ta= 15° C	> 500,000 h (L70)
Lifetime at Ta= 40° C	253,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:



Interior LED ceiling and wall luminaires

	LED	A	B
78635 ADA	11.6W	11 3/4	3 5/8

