

LED pole-top luminaires with asymmetrical light distribution

Housing/fitter: Die-cast aluminum construction. The luminaire slip fits a 3" O.D. pole top or tenon and is secured by six (6) socket head stainless steel screws threaded into stainless steel inserts. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Clear acrylic diffuser held in place by die-cast aluminum frame. Fully gasketed for weather tight operation using a molded silicone gasket.

Electrical: 23.6W LED luminaire, 28 total system watts, -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.


CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

Weight: 21.4 lbs.

EPA (Effective projection area): 0.73 sq. ft.

Luminaire Lumens: 2297

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



Pole-top luminaires

	LED	A	B
84 121	23.6W	20 ⁵ / ₈	22 ¹ / ₄

*Recommended for use with 12' to 18' poles