

Application

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas and plazas. Provided with slip fitter to fit 3" O.D. poles.

Materials

Luminaire housing and pole fitter constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear acrylic diffuser with optical texture
Reflector made of pure anodized aluminum
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Effective projection area: 1.61 sq. ft.
Weight: 61.7 lbs

Electrical

Operating voltage	120-277V
Minimum start temperature	-30° C
Maximum ambient temperature	35° C
LED module wattage	44.4 W
System wattage	52 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	5,099 lumens (4000K)
LED service life (L70)	60,000 hours

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Pole-top luminaire · symmetric			
	LED	A	B
84 147	46.4W	29 1/2	33 1/8

* Recommended for use with 18' to 20' poles

Type:
BEGA Product:
Project:
Modified:

