

**Application**

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas, roadways and walkways. Provided with slip fitter to fit 3" O.D. poles.

**Materials**

Luminaire housing and pole fitter constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Clear acrylic diffuser with optical texture  
 Reflector made of pure anodized aluminum  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations

Protection class IP65

Effective projection area: 1.61 sq. ft.

Weight: 61.7 lbs

**Electrical**

Operating voltage	120-277V
Minimum start temperature	-30° C
Maximum ambient temperature	35° C
LED module wattage	47.2W
System wattage	52W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	4,557 lumens (3000K)
LED service life (L70)	60,000 hours

**LED color temperature**


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



**Pole-top luminaire · asymmetric**

	LED	A	B
<b>84 148</b>	47.2W	29 1/2	33 1/2

\* Recommended for use with 18' to 20' poles

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

