Type:
BEGA Product:
Project:
Modified:

Application
LED pole-top luminaires with symmetrical light distribution ideal for illuminating squares, plazas and other open spaces. Provided with slip fitter to fit 3" O.D. poles.

Materials
Luminaire housing and constructed of die-cast and spun marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Clear safety glass
Reflector made of pure anodized aluminum
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 32.2 lbs.

EPA (Effective projection area): 1.5 sq. ft.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-35° C
LED module wattage	23.4 W
System wattage	27.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2,077 lumens (4000K)
Lifetime at Ta = 15° C	420,000 h (L70)
Lifetime at Ta = 45° C	190,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Pole-top · Symmetrical

	LED	A	B
84 401	23.4 W	28	14 ¼

Recommended for use with 14' to 16' poles.

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2018