

Application

LED pole-top luminaires with symmetrical light distribution ideal for illuminating squares, plazas and other open spaces. Provided with slip fitter to fit 3" O.D. poles.

Materials

Luminaire housing and constructed of die-cast and spun marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Clear safety glass  
Reflector made of pure anodized aluminum  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Effective projection area: 1.5 sq. ft.  
Weight: 32.2 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	47.4 W
System wattage	56.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	3,695 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 45° C	108,000 h (L70)

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Pole-top · Symmetrical			
	LED	A	B
<b>84 402</b>	47.4 W	28	14 ¼

Recommended for use with 16' to 20' poles.

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2018 Updated 01/18/19

Type:  
BEGA Product:  
Project:  
Modified:

