

LED garden and pathway bollard - unshielded - direct burial anchorage

BEGA

Application

LED bollard luminaires with unshielded light distribution and safety guard designed for use in the illumination of gardens and residential installations. Provided with mounting system that allows the luminaire to be installed in direct bury soil applications.

Materials

Luminaire housing, tube and base plate constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Crystal glass, inside white
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Anchorage constructed of galvanized steel

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 10.0lbs

Electrical

Operating voltage	12V AC (remote magnetic transformer req.)
LED module wattage	2.9W
System wattage	4.4 W
Color rendering index	Ra > 90
Luminaire lumens	262 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 50° C	302,000 h (L70)

LED color temperature
3000K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) Bronze (BRZ)



LED garden and pathway bollard · unshielded				
	LED	A	B	Anchorage
84 605	2.9W (12V AC)	4 3⁄8 x 4 3⁄8	31 3⁄8	Direct burial



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2018 Updated 02/14/18