

Application

LED bollard luminaires with unshielded light distribution and safety guard designed for use in the illumination of gardens and residential installations. Provided with mounting system that allows for the direct attachment to hardscape such as concrete, pavers or decking.

Materials

Luminaire housing, tube and base plate constructed of die-cast and extruded marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
Crystal glass, inside white  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Anchorage constructed of galvanized steel

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 10.0lbs

Electrical

Operating voltage	12V AC (remote magnetic transformer req.)
LED module wattage	2.9W
System wattage	4.4 W
Color rendering index	Ra > 90
Luminaire lumens	262 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 50° C	302,000 h (L70)

**LED color temperature**  
3000K

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors     Black (BLK)     Bronze (BRZ)



LED garden and pathway bollard · unshielded				
	LED	A	B	Anchorage
84 607	2.9W (12V AC)	4 3⁄8 x 4 3⁄8	31 3⁄8	Included

