

LED garden and pathway bollard - unshielded with guard - direct burial anchorage

BEGA

Application

LED bollard luminaires with unshielded 360° light distribution and safety guard designed for use in the illumination of gardens and residential installations. Provided with mounting system that allows the luminaire to be installed in direct bury soil applications.

Materials

Luminaire housing and tube constructed of die-cast and extruded marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Three-ply opal glass
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Anchorage constructed of galvanized steel

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 8.9lbs

Electrical

Operating voltage	12V AC (remote magnetic transformer req.)
LED module wattage	2.9W
System wattage	4.4W
Color rendering index	Ra > 90
Luminaire lumens	206 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 50° C	226,000 h (L70)

LED color temperature
3000K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) Bronze (BRZ)

Type:
BEGA Product:
Project:
Modified:



LED garden and pathway bollard · unshielded with guard				
	LED	A	B	Anchorage
84 608	2.9W (12V AC)	4 3⁄8	27 7⁄8	Direct burial

