

Application

LED bollard with unshielded symmetric light distribution. Designed for landscapes, pathways, and open spaces, these robust luminaires can delineate and structure exterior spaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Luminaire housing constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 White acrylic diffuser
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 10.6lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	7.6W
System wattage	9.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	851 lumens (3000K)
Lifetime at Ta = 15° C	140,000 h (L70)
Lifetime at Ta = 55° C	65,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Bollard · unshielded

	LED	A	B	Anchorage
84 666	7.6W	4 ¾	31 ½	79 824

Type:
 BEGA Product:
 Project:
 Modified:

