

LED bollards with asymmetrical shielded light distribution

Post construction: One-piece extruded aluminum with a one-piece die-cast aluminum top housing and base internally welded into an assembly. Die-castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Two piece die-cast aluminum optical enclosure secured to bollard post by two (2) mechanically captive stainless steel screws threaded into stainless steel inserts. White safety glass. Reflector made of pure anodized aluminum. Fully gasketed for weather tight operation using molded silicone gasket.

Electrical: 14.5 total luminaire system watts, 12.3W LED. -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with a >80 CRI. Available in 4000K (>80 CRI); add suffix K4 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.


Anchor base: Heavy galvanized steel mounting base, slotted for precise alignment. Mounts to BEGA 79 825 anchorage kit. Bollard secures to base with two (2) stainless steel set screws.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

Weight: 26.7 lbs

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



Asymmetrical shielded

	Lamp	A	B	C	Wiring box
84 672	12.3W LED	13 ³ / ₈	31 ¹ / ₂	4"	79 825

