

Application

LED bollards with 360° light distribution in stainless steel. This luminaire is designed to illuminate paths, entrances and driveways in private and public areas.

Materials

- Luminaire housing constructed 316 grade stainless steel
- Borosilicate glass lens
- Top reflector made of pure anodized aluminum
- Cone reflector made of blasted stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Mounting plate and anchorage constructed of stainless steel

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 38.6 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	16.5 W
System wattage	19.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1481 lumens (3000K)
Lifetime at Ta = 15° C	53,000 h (L70)
Lifetime at Ta = 25° C	50,000 h (L70)


LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel.
 Custom colors are not available.
 Stainless steel requires regular cleaning and maintenance, much like household appliances to maintain its luster and prevent tarnishing or the appearance of rust like stains.



Stainless steel bollard · shielded					
	LED	A	B	C	Anchorage
88061	16.5 W	8 7/8	43 7/8	11 7/8	79818



Type:
 BEGA Product:
 Project:
 Modified: