

Application

Light Building Elements are luminous design features for public areas. These luminaires are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances, and atria.

Materials

Luminaire housing and post constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 UV stabilized acrylic diffuser
 Reflector made of pure anodized aluminum
 Silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65

Weight: 77.6lbs.

EPA (Effective projection area): 11.84 sq. ft.

Electrical

Operating voltage 120-277VAC (surge protection)
 Minimum start temperature -40°C
 Maximum ambient temperature 45°C
 LED module wattage 31.0W
 System wattage 36.0W
 Controllability 0-10V dimmable
 Color rendering index $Ra > 80$
 Luminaire lumens 3,279 lumens (4000K)
 LED service life (L70) 60,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL:
 Bronze (BRZ) Silver (SLV) CUS:



Light Building Element · asymmetric wide beam

	LED	A	B	C	D
88 067	31.0W	6 $\frac{5}{8}$	23 $\frac{3}{8}$	177	31 $\frac{1}{2}$

Type:
 BEGA Product:
 Project:
 Modified:

