

Pole top luminaires with widespread distribution

Housing/fitter: Lower slip fitter is made from a single die-cast aluminum part which includes four support arms and the lower diffuser frame. The fixture slip fits a 3" O.D. pole top or tenon and is secured by four stainless steel set screws. The top portion of the lamp housing is made from heavy gauge spun aluminum. Relamping is achieved by removing a single threaded fastener at the top of the fixture. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: 16.0W LED luminaire, 19 total system watts, -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

Note: Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.


UL listed for US and Canadian Standards, suitable for wet locations. Protection class: IP65.

Weight: 25.5 lbs.

EPA (Effective projection area): 1.0 sq. ft.

Luminaire Lumens: 1890

Type:
 BEGA Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



	Lamp	LEED	A	B
88260	26W LED	LZ-2	27 $\frac{1}{2}$	12 $\frac{5}{8}$

Recommended for use with 14' to 16' poles.

