

Application

LED bollard with fully shielded light distribution. The glare-free illumination of these luminaires is ideally suited for lighting entrances and footpaths as well as many areas of garden and landscape architecture.

Materials

Luminaire housing and base constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear safety glass with optical texture
Reflector made of pure anodized aluminum
High temperature silicone gasket
Mechanically captive stainless steel fastener

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 9.3lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	20.6 W
System wattage	25.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1577 lumens (3000K)
Lifetime at Ta = 15° C	>500,000 h (L70)
Lifetime at Ta = 50° C	280,000 h (L70)

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED bollard · symmetric					
	LED	A	B	C	Anchorage
88 262	20.6 W	10	21 1/2	4 3/8	79 824

Type:
BEGA Product:
Project:
Modified:

