

Pole top luminaires with widespread distribution

Housing/fitter: Lower slip fitter is made from a single die-cast aluminum part which includes four support arms and the lower diffuser frame. The fixture slip fits a 3" O.D. pole top or tenon and is secured by four stainless steel set screws. The top portion of the lamp housing is made from heavy gauge spun aluminum. Relamping is achieved by removing a single threaded fastener at the top of the fixture. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: 25.2W LED luminaire, 30.0 total system watts, -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.



CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

Weight: 25.4 lbs.

EPA (Effective projection area): 1.1 sq. ft.

Luminaire Lumens: 2580

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



Pole-top luminaires · Fig. right			
	Lamp	A	B
88 263	25.2 W LED	27 1/2	12 5/8